



# TECHNICAL DATA SHEET

## DEEP SCRUB RECOATING CLEANER

### DESCRIPTION

Armor Plate Deep Scrub & Recoating Cleaner is a heavy-duty, water based cleaning concentrate designed for scrub / re-coat maintenance procedures. It is ideal for use in automatic scrubbers equipped with proper floor pad or brush. Using a neutral pH range formulation, Armor Plate Deep Scrub & Recoating Cleaner aggressively removes embedded soils and scuffs in upper layers of finish film, and prepares the surface for re-coating with a minimum of rinsing, saving time and labour.

### PRODUCT FEATURES / BENEFITS

- Neutral range pH formulation
- Aggressively removes embedded soils / scuffs
- Reduced rinsing saves time and labour
- Use with standard floor machine or with automatic scrubber

### DIRECTIONS FOR USE

#### DILUTE PRODUCT AS FOLLOWS:

Moderate soil /build-up	Dilute 1 part AP Deep Scrub Recoating Cleaner to 25 parts of warm water
Light finish removal	
Heavy soil /build-up	Dilute 1 part AP Deep Scrub Recoating Cleaner to 12 parts of warm water
Moderate finish removal	

After scrubbing, remove solution from floor with wet-dry vacuum or a clean mop. Damp mop rinse with clear water to remove any excess residue. Allow floor to completely dry prior to re-coating.

#### SCRUB/RE-COAT USING AUTOMATIC SCRUBBER:

Dilute AP Deep Scrub Recoating Cleaner in mop bucket according to above dilution directions. Liberally mop solution onto floor surface and allow to dwell for 1 to 4 minutes (depending on how deeply it is desired to scrub). Fill auto-scrubber with clear water, mount scrubbing pad or medium grade brush. With vacuum off and squeegee up, scrub the floor until all embedded soils and scuffs are removed from finish. Lower squeegee and vacuum all scrubbing solution. Using clear water from the auto-scrubber, rinse floor to remove any excess residue. Allow floor to completely dry prior to re-coating.

#### SCRUB/RE-COAT USING STANDARD 175 RPM FLOOR MACHINE:

Dilute AP Deep Scrub Recoating Cleaner in mop bucket according to above dilution directions. Liberally mop solution onto floor surface and allow to dwell for 1 to 4 minutes (depending on how deeply it is desired to scrub). With machine and scrub floor pad or brush, scrub surface of floor until all embedded soils and scuffs are removed from finish.

### SPECIFICATIONS

Colour .....	Pink	Flash Point .....	None
Odour .....	Pleasant	Biodegradable .....	Yes
Actives (%) .....	18.2 ± 0.3	Specific Gravity (gr/cc) .....	1.020 ± .002
pH (Concentrate) .....	9 ± 0.2	Density (lbs/gal) .....	8.51 ± .015
pH (Use Dilution) .....	7.4 ± 0.2	Free Rinsing .....	Yes
Upper Cloud .....	> 140°F	Non Corrosive .....	Yes
Lower Cloud .....	< 25°F	Shelf Life .....	1 year minimum in original unopened container

### SAFETY INFORMATION

**CAUTION:** HARMFUL IF SWALLOWED. MAY CAUSE SKIN AND EYE IRRITATION. KEEP OUT OF REACH OF CHILDREN. Avoid contact with skin and eyes. Do not ingest. May cause gastric distress.

**FIRST AID: For Eyes:** Flush eyes with water for at least fifteen minutes. Seek medical attention. **For Skin:** Flush

skin thoroughly with water and apply emollient cream. If irritation persists, seek medical attention. **If ingested:** Do not induce vomiting. Give milk, egg white, gelatine or water. Seek immediate medical attention. Never give anything by mouth to an unconscious person. **FOR PROFESSIONAL USE ONLY**



CLEANER



ABN 57 119 951 307

17 Yale Drive, EPPING VIC 3076

PH: 03 9408 8699 FAX: 03 9408 8399

EMAIL: [info@chemeco.com.au](mailto:info@chemeco.com.au) WEB: [www.chemeco.com.au](http://www.chemeco.com.au)