



FLOOR SEALER FINISH

DESCRIPTION

Armor Plate Floor Sealer Finish is a highly advanced floor finish with superior “off-the-mop” initial gloss. This ultra-high solids formula provides exceptional film clarity, repels soil and scratches, and extends the time between stripping cycles from 18 to 36 months. A wet-look gloss floor finish incorporating proprietary polymer technology producing outstanding long-term clarity, excellent abrasion resistance and extended durability. Excellent scrub and re-coat performance easily extends the time between stripping cycles from 18 to 36 months.

PRODUCT FEATURES / BENEFITS

- Easy to Apply / Dries quickly, levels beautifully, no re-coat attack
- Ultra-High Solids / Save time and labour with fewer coats
- Scuff, scratch and abrasion resistant / Minimizes maintenance requirements
- Repels Dirt / Stays clean, clear and bright longer
- Highest “Off-The-Mop” Gloss / Floors look beautiful, right from the start
- Excellent Burnish Response / Easily maintain wet-look gloss for extended period of time
- Exclusive Micro Molecular Technology/ Superior durability, extremely consistent surface excel at long term performance

DIRECTIONS FOR USE

Floor Preparation: Using Superior Stripper, No-Rinse, No-Scrub Liquifying Stripper, strip off old finish, paying particular attention to areas under furniture, and build-up areas. Remove all stripping solutions from floor with mop or wet dry vacuum. If necessary, rinse thoroughly with clean water and allow to completely dry.

Application: Using a clean mop or applicator apply thin uniform coats of Armor Plate Floor Sealer Finish. Allow to dry for a minimum of 30 minutes after each coat. Do not apply more than 4 coats in a 24 hour period. Floor should be thoroughly dry before traffic is allowed in area.

Buffing and Burnishing: Armor Plate Floor Sealer Finish is ideal for use in no-buff or buffing programs using all speeds of

buffing or burnishing machines.

For spray buffing, mop-on or auto-scrubber restoring use Armor Plate Gloss Restorer.

Routine Maintenance: Damp mop or clean with an automatic scrubber using Armor Plate Neutral Floor Cleaner following label directions.

Scrub and Re-coat: When routine maintenance and buffing/burnishing no longer responds as needed, scrub and re-coat using Armor Plate Deep Scrub and Re-coating Cleaner following label directions.

SPECIFICATIONS

Type Pure acrylic polymers
 Non Volatile Solids (%)..... 25.5 ± 0.5
 pH..... 8.5 ± 0.5
 Coverage (sq.m./litre)..... 55
 Drying Time (minutes)..... 30
 % Styrene (Free Monomer) 0.0

Specific Gravity (gr/cc) 1.034 ± .005
 Colour White, opaque liquid
 Odour..... Typical acrylic
 Powdering..... None
 Flash Point..... None
 Slip Resistant..... Yes
 Shelf Life1 year minimum in original unopened container

SAFETY INFORMATION

CAUTION: MAY BE HARMFUL IF SWALLOWED. MAY CAUSE SKIN AND EYE IRRITATION. KEEP OUT OF REACH OF CHILDREN. Avoid contact with skin and eyes. Do not ingest. If ingested, may cause severe gastric distress and blockage.

FIRST AID: For Eyes: Flush eyes with water for at least fifteen minutes. If irritation persists seek medical attention. For Skin:

Wash thoroughly with soap and water. If irritation persists seek medical attention. **If ingested:** Do not induce vomiting. Give large quantities of water. Seek medical attention. Never give anything by mouth to an unconscious person.

KEEP FROM FREEZING

FOR PROFESSIONAL USE ONLY



FLOOR CARE



ABN 57 119 951 307

17 Yale Drive, EPPING VIC 3076

PH: 03 9408 8699 FAX: 03 9408 8399

EMAIL: info@chemeco.com.au WEB: www.chemeco.com.au

| HMIS HAZARD CODE | |
|------------------|---------------------|
| 1 | HEALTH |
| 0 | FLAMMABILITY |
| 0 | REACTIVITY |
| 0 | PERSONAL PROTECTION |