



TECHNICAL DATA SHEET

SEALER

DESCRIPTION

A technologically advanced hard surface sealer recommended for resilient tile, terrazzo and quarry tile floors. This proprietary hybrid polymer system provides a uniform, smooth surface maximizing light reflection when a quality floor finish is applied over the sealer. This unique, water-based sealer creates a barrier against hydrophobic stains such as asphalt/coal tar (commonly tracked in through parking lots/construction sites) and anti-oxidants (present in the backing of walk-off mats). Many organic stains are also repelled such as urine, coffee, tea, mustard, ketchup, etc.

PRODUCT FEATURES / BENEFITS

- Semi-Permanent Sealer / Significant labour & material savings
- Not removed with normal floor stripping / Ideal for asbestos tile floor care program
- Water-based Emulsion / No toxic fumes & easy to use
- Provides Uniform Floor Surface / Maximizes gloss of subsequent coatings of floor finish
- Stain Resistant / Prevents replacement of floor tiles

DIRECTIONS FOR USE

Floor Preparation: Strip floor thoroughly with SUPERIOR STRIPPER making sure all previous sealers and finishes are removed. Rinse completely and allow to dry.

Application of Sealer: Use a synthetic mop or applicator. Apply "one" uniform coat of ARMOR PLATE Sealer and allow to dry and cure for 60 minutes (on quarry tile apply two uniform coats). After ARMOR PLATE Sealer is thoroughly cured apply five coats of floor finish in normal manner over a 48 hour period.

Sealer Removal: This semi-permanent sealer can be stripped with SUPERIOR STRIPPER after all floor finish has been removed.

Stain Removal: Remove all floor polish with SUPERIOR STRIPPER Remove stain with a Water-Based Degreaser Cleaner or other Heavy Duty Cleaner. Make sure to remove stains as soon as possible to prevent permanent damage to floor surface.

SPECIFICATIONS

Solids (%).....	22.0 ± 0.5	Flash Point	None
Colour.....	White	Curing Time (minutes).....	60
pH.....	8.0	Levelling	Excellent
Specific Gravity(gr/cc).....	1.02	Stain Resistance	Excellent
Density (lbs/gal).....	8.512	Durability.....	Excellent
Viscosity (cps).....	< 10	Anti-Slip.....	Yes
Polymer Type.....	Unique Hybrid	Coverage (sq. ft./gal)	1000 - 2500
Solubility.....	Complete in water	Freeze Thaw Stability.....	Passes 3 cycles
Odour	Mildly Pleasant	Shelf Life	1 year minimum in original unopened container

SAFETY INFORMATION

CAUTION: MAY BE HARMFUL IF SWALLOWED. MAY CAUSE SKIN AND EYE IRRITATION. KEEP OUT OF REACH OF CHILDREN. Avoid contact with eyes. Do not ingest. If ingested, may cause severe gastric distress and blockage.

FIRST AID: For Skin: Wash thoroughly with soap and water. If irritation persists seek medical attention. **If ingested:** Do not

induce vomiting. Give large quantities of water. Seek medical attention. Never give anything by mouth to an unconscious person.

Meets or exceeds 0.5 coefficient of friction as measured by James Machine Methodology ASTM Method D 2047-82.
KEEP FROM FREEZING FOR PROFESSIONAL USE ONLY



FLOOR CARE



ABN 57 119 951 307

17 Yale Drive, EPPING VIC 3076

PH: 03 9408 8699 FAX: 03 9408 8399

EMAIL: info@chemeco.com.au WEB: www.chemeco.com.au

HMIS HAZARD CODE	
1	HEALTH
0	FLAMMABILITY
0	REACTIVITY
0	PERSONAL PROTECTION