

Chemwatch: 1823

Version No: 10.1.1.1 Safety Data Sheet according to WHS and ADG requirements Chemwatch Hazard Alert Code: 4

Issue Date: 27/06/2022 Print Date: 05/03/2023 S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	CHEMECO CAUSTIC SODA
Chemical Name	sodium hydroxide
Synonyms	76634, 78064, Caustic Flake, NaOH, PPG Pels Caustic Soda Beads, Spectrum S1303 S1302 S1303 S1305 S1308 SO170, caustic soda - pearl solid grades 30167, caustic soda, anhydrous, lye, soda lye, sodium hydroxide granulated, sodium hydroxide monohydrate (CAS RN: 12200-64-5), sodium hydroxide solid pellets pearl flakes alkali, white caustic soda
Proper shipping name	SODIUM HYDROXIDE, SOLID
Chemical formula	H2O.HNaO HNaO
Other means of identification	Not Available
CAS number	1310-73-2

Relevant identified uses of the substance or mixture and uses advised against

Compone	nt of alkali cleaners. Manufacture of soap, pulp and paper; rayon. Chemical manufacture. Neutralising agent in petroleum refining; manufacture of
Relevant identified uses	
	aluminium, detergents, textile processing, refining of vegetable oils.

Details of the supplier of the safety data sheet

Registered company name	Chemeco (Aust)
Address	17 Yale Drive Epping VIC 3076
Telephone	+61 3 9408 8699
Fax	+61 3 9408 8399
Website	https://www.chemeco.com.au/
Email	info@chemeco.com.au

Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Poisons Schedule	S6
[2] Classification	Metal Corrosion Category 1, Skin Corrosion/Irritation Category 1A
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI
Label elements	
GHS label elements	
SIGNAL WORD	DANGER
Hazard statement(s)	
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.

Precautionary statement(s) Prevention

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P234	Keep only in original container.
Precautionary statement(s) Response	

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.

Precautionary statement(s) Storage

P405 Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances CAS No %[weight] Name 1310-73-2 >98 sodium hydroxide

Mixtures

See section above for composition of Substances

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor. Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested. Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. This must definitely be left to a doctor or person authorised by him/her. (ICSC13719)
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

For acute or short-term repeated exposures to highly alkaline materials:

• Respiratory stress is uncommon but present occasionally because of soft tissue edema.

• Unless endotracheal intubation can be accomplished under direct vision, cricothyroidotomy or tracheotomy may be necessary.

Oxygen is given as indicated.

• The presence of shock suggests perforation and mandates an intravenous line and fluid administration.

Damage due to alkaline corrosives occurs by liquefaction necrosis whereby the saponification of fats and solubilisation of proteins allow deep penetration into the tissue.

Alkalis continue to cause damage after exposure.

INGESTION:

Milk and water are the preferred diluents

No more than 2 glasses of water should be given to an adult.

- Neutralising agents should never be given since exothermic heat reaction may compound injury.
- * Catharsis and emesis are absolutely contra-indicated.
- * Activated charcoal does not absorb alkali.
- * Gastric lavage should not be used.

Supportive care involves the following:

- Withhold oral feedings initially.
- If endoscopy confirms transmucosal injury start steroids only within the first 48 hours.
- Carefully evaluate the amount of tissue necrosis before assessing the need for surgical intervention.
- Patients should be instructed to seek medical attention whenever they develop difficulty in swallowing (dysphagia).

SKIN AND EYE:

Injury should be irrigated for 20-30 minutes.

Eye injuries require saline. [Ellenhorn & Barceloux: Medical Toxicology]

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- Water spray or fog.
- ▶ Foam.
- Dry chemical powder.
- BCF (where regulations permit).

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
Advice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use fire fighting procedures suitable for surrounding area.
Fire/Explosion Hazard	 Non combustible. Not considered a significant fire risk, however containers may burn. Decomposition may produce toxic fumes of:, metal oxidesMay emit corrosive fumes Solid. in contact with water or moisture reacts violently, and solutions are highly alkaline and may cause severe skin burns.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

 Remove all ignition sources. Clean up all spills immediately. Avoid contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material. Check regularly for spills and leaks.
 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs.
	 Use in a well-ventilated area. WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material.
Other information	 Plastic bag NOTE: Bags should be stacked, blocked, interlocked, and limited in height so that they are stable and secure against sliding or collapse. Store in original containers. Keep containers securely sealed.
	 Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. DO NOT store near acids, or oxidising agents No smoking, naked lights, heat or ignition sources.

Conditions for safe storage, including any incompatibilities

Suitable container	 Glass container is suitable for laboratory quantities DO NOT use aluminium, galvanised or tin-plated containers
	 Lined metal can, lined metal pail/ can. Plastic pail.

	 * Polyliner drum. * Packing as recommended by manufacturer. For low viscosity materials * Drums and jerricans must be of the non-removable head type. * Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): * Cans with friction closures and * low pressure tubes and cartridges may be used.
Storage incompatibility	 Sodium hydroxide/ potassium hydroxide: reacts with water evolving heat and corrosive fumes reacts with water evolving heat and corrosive fumes reacts violently with acids, trans-acetylene dichloride, aminotetrazole, p-bis(1,3-dibromoethyl), benzene, bromoform, halogenated compounds, nitrogen-containing compounds, organic halogens, chlorine dioxide ((explodes), chloroform, cresols, cyclopentadiene, 4-chloro-2-methylphenol, cis-dichloroethylene, 2,2-dichloro-3,3-dimethylbutane, ethylene chlorohydrin, germanium, iodine pentafluoride, maleic anhydride, p-nitrotoluene, nitrogen trichloride, o-nitrophenol, phosphonium iodide, potassium peroxodisulfate, propylene oxide, 1,2,4,5- tetrachlorobenzene (highly toxic substance is forme), 2,2,3-3-tetrafluoro-1-propanol, tetrahydrofuran, thorium dicarbide, trichloroethanol, 2,4,6-trinitrotoluene, vinyl acetate reacts with fluorine, nitroalkanes, (forming explosive compounds) incompatible with acetic acid, acetaldehyde, acetic anhydride, acrolen, acrylontrile, ally chloride, organic anhydride, acrylates, alcohols, aldehydes, akylene oxides, substituted allys, ammonium chlorophatinate, benzaren-1/4-diol, carbon dioxide, cellulose nitrate, chlorio trifluoride, 4-chlorobutyronitrile, chlorohydrin, chloronitrotoluenes, chlorosulfonic acid, cinnamaldehyde, caprolactam solution, chlorocresols, 1,2-dichloroethylene, epichlorohydrin, ethylene cyanohydrix, formaldehyde (forms formic acid and flammable hydrogen gas), glycols, glyoxal, hexachloropelatinate, hydrogen sulfide, hydrogen sulfide, hydrogen sulfide, bydrogen sulfide, bydrogen sulfide, protoxide vita acids (forming corracesponding sall), nitrobenzene, N-nitrosohydroxylamine, nitrates pentol, phenols, phenols, phosphorus, phosphorus pentaoxide, beta-propiolactone, sodium, sulfur dioxide, tetrahydroborate, 1,1,1,2-tetrachloroethane, 2,2,2-trichloroethanol, trichlororitromethane, zircon

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

		TWA	STEL		Peak	Notes
ium hydroxide Sodium	hydroxide	Not Available	Not Ava	ailable	2 mg/m3	Not Available
EMERGENCY LIMITS						
erial name	TEEL-1		TEEL-2		TEE	L-3
ium hydroxide	Not Available		Not Availab	le	Not	Available
Ingredient Original IDLH Revised IDLH						
250 mg/m3			10 mg/m3			
e iu gi	rial name Im hydroxide nal IDLH	rial name TEEL-1 Im hydroxide Not Available nal IDLH	rial name TEEL-1 Im hydroxide Not Available	rial name TEEL-1 TEEL-2 Im hydroxide Not Available Not Available Revised IDLH	rial name TEEL-1 TEEL-2 m hydroxide Not Available Not Available nal IDLH Revised IDLH	rial name TEEL-1 TEEL-2 TEE Im hydroxide Not Available Not Available Not nal IDLH Revised IDLH

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. If conditions where worker exposure potential is high, wear full-face air-supplied breathing apparatus and full protective suit.			
Personal protection				
Eye and face protection	 Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure. Chemical goggles.whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted. Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection. Alternatively a gas mask may replace splash goggles and face shields. 			
Skin protection	See Hand protection below			
Hands/feet protection	 Elbow length PVC gloves The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. 			

	The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Suitability and durability of glove type is dependent on usage.
Body protection	See Other protection below
Other protection	 Overalls. PVC Apron. PVC protective suit may be required if exposure severe. Eyewash unit.
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

NV CHEMICALS CAUSTIC SODA (SODIUM HYDROXIDE)

Material	CPI
BUTYL	А
NAT+NEOPR+NITRILE	A
NATURAL RUBBER	A
NATURAL+NEOPRENE	A
NEOPRENE	А
NEOPRENE/NATURAL	A
NITRILE	A
NITRILE+PVC	A
PE	A
PE/EVAL/PE	A
PVC	A
SARANEX-23	A
SARANEX-23 2-PLY	A
TEFLON	A
VITON/CHLOROBUTYL	A

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove,

a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Respiratory protection

Particulate. (AS/NZS 1716 & 1715, EN 143:000 & 149:001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	-	PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

* - Negative pressure demand ** - Continuous flow

 $\begin{array}{l} \mathsf{A}(\mathsf{AII}\ \mathsf{classes}) = \mathsf{Organic}\ \mathsf{vapours},\ \mathsf{B}\ \mathsf{AUS}\ \mathsf{or}\ \mathsf{B1} = \mathsf{Acid}\ \mathsf{gasses},\ \mathsf{B2} = \mathsf{Acid}\ \mathsf{gas}\ \mathsf{or}\ \mathsf{hydrogen}\ \mathsf{cyanide}(\mathsf{HCN}),\ \mathsf{B3} = \mathsf{Acid}\ \mathsf{gas}\ \mathsf{or}\ \mathsf{hydrogen}\ \mathsf{cyanide}(\mathsf{HCN}),\ \mathsf{B3} = \mathsf{Acid}\ \mathsf{gas}\ \mathsf{or}\ \mathsf{hydrogen}\ \mathsf{cyanide}(\mathsf{HCN}),\ \mathsf{B3} = \mathsf{Acid}\ \mathsf{gas}\ \mathsf{or}\ \mathsf{hydrogen}\ \mathsf{cyanide}(\mathsf{HCN}),\ \mathsf{B4} = \mathsf{Sulfur}\ \mathsf{dioxide}(\mathsf{SO2}),\ \mathsf{G} = \mathsf{Agricultural}\ \mathsf{chemicals},\ \mathsf{K} = \mathsf{Ammonia}(\mathsf{NH3}),\ \mathsf{Hg} = \mathsf{Mercury},\ \mathsf{NO} = \mathsf{Oxides}\ \mathsf{of}\ \mathsf{nitrogen},\ \mathsf{MB} = \mathsf{Methyl}\ \mathsf{bromide},\ \mathsf{AX} = \mathsf{Low}\ \mathsf{boiling}\ \mathsf{point}\ \mathsf{organic}\ \mathsf{compounds}(\mathsf{below}\ \mathsf{65}\ \mathsf{degC}) \\ \end{array}$

- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program. Use
- approved positive flow mask if significant quantities of dust becomes airborne.
- Try to avoid creating dust conditions.

Appearance	White hygroscopic, odourless, pellets, flakes, stic added to hot water. Reacts violently with acid	• •	en mixed with water. Explosive boiling and spitting will occur
Physical state	Divided Solid	Relative density (Water = 1)	2.12 @ 20 C
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	Not Applicable	Decomposition temperature	Not Applicable
Melting point / freezing point (°C)	318.4	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	1390	Molecular weight (g/mol)	40
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	< 2 (20 C)	Gas group	Not Available

Continued...

Solubility in water (g/L) Miscible pH as a solution (1%) 12.7; (5%) Vapour density (Air = 1) 2.3 (hydrate) VOC g/L Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

	9			
Inhaled	Inhaling corrosive bases may irritate the respiratory tract. Symptoms include cough, choking, pain and damage to the mucous membrane. Sudden inhalation of sodium hydroxide dust may produce fatal outcome such as spasm, inflammation of the throat and airway, burns, severe lung inflammation and fluid accumulated in the lungs These manifest as coughing, wheezing, shortness of breath, headache, nausea and vomiting. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.			
	The material can cause respiratory irritation in some persons. The body	's response to such irritation can cause further lung damage.		
Ingestion	Ingestion of alkaline corrosives may produce burns around the mouth, ulcerations and swellings of the mucous membranes, profuse saliva production, with an inability to speak or swallow. Both the oesophagus and stomach may experience burning pain; vomiting and diarrhoea may follow. Accidental ingestion of the material may be damaging to the health of the individual. Ingestion of sodium hydroxide may result in severe pain, burns to the mouth, throat, stomach, nausea and vomiting, swelling of the throat and subsequent perforation of the gastro-intestinal tract and suffocation but a 1% solution (pH 13.4) of sodium hydroxide in water failed to cause any damage of the stomach or gullet in rabbits.			
Skin Contact	The material can produce severe chemical burns following direct contact with the skin. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Sodium hydroxide causes burns which may take time to manifest and cause pain, thus care should be taken to avoid contamination of gloves and boots. A 5% aqueous solution of it produces tissue death on rabbit skin while 1% solution caused no effect on irrigated rabbit eye. Skin contact with alkaline corrosives may produce severe pain and burns; brownish stains may develop. The corroded area may be soft, gelatinous and necrotic; tissue destruction may be deep. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. The material may cause severe inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.			
Eye	If applied to the eyes, this material causes severe eye damage. Direct eye contact with corrosive bases can cause pain and burns. There may be swelling, epithelium destruction, clouding of the cornea and inflammation of the iris. Mild cases often resolve; severe cases can be prolonged with complications such as persistent swelling, scarring, permanent cloudiness, bulging of the eye, cataracts, eyelids glued to the eyeball and blindness.			
Chronic	Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis, caused by particles less than 0.5 micron penetrating and remaining in the lung.			
	TOVICITY	IDDITATION		
		IRRITATION		
	Oral (rabbit) LD50: 325 mg/kg ^[1]	Eye (rabbit): 0.05 mg/24h SEVERE		
sodium hydroxide		Eye (rabbit):1 mg/24h SEVERE		
		Eye (rabbit):1 mg/30s rinsed-SEVERE		
		Skin (rabbit): 500 mg/24h SEVERE		
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute to specified data extracted from RTECS - Register of Toxic Effect of chem			
-				
SODIUM HYDROXIDE	The material may produce severe irritation to the eye causing pronound may produce conjunctivitis. The material may cause severe skin irritation after prolonged or repeate production of vesicles, scaling and thickening of the skin. Repeated exp	ed exposure and may produce on contact skin redness, swelling, the osures may produce severe ulceration.		
	Asthma-like symptoms may continue for months or even years after exposure to the airways dysfunction syndrome (RADS) which can occur following exposure to high la absence of preceding respiratory disease, in a non-atopic individual, with abrupt ons exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence	evels of highly irritating compound. Key criteria for the diagnosis of RADS include the tet of persistent asthma-like symptoms within minutes to hours of a documented		

	on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS.				
Acute Toxicity	×	Carcinogenicity	0		
Skin Irritation/Corrosion	×	Reproductivity	0		
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0		
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0		
Mutagenicity	0	Aspiration Hazard	0		
		Legend: 🗙	- Data available but does not fill the criteria for classification		

🐓 – Data required to make classification available S – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
sodium hydroxide	LC50	96	Fish	4.16158mg/L	3
sodium hydroxide	EC50	48	Crustacea	40.4mg/L	2
sodium hydroxide	EC50	96	Algae or other aquatic plants	1034.10043mg/L	3
sodium hydroxide	EC50	384	Crustacea	27901.643mg/L	3
sodium hydroxide	NOEC	96	Fish	56mg/L	4
	Extracted from 1 II II	Extracted from 1. II.ICI.ID. Toxicity. Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN			

Legend:

Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

For Metal:

Atmospheric Fate - Metal-containing inorganic substances generally have negligible vapour pressure and are not expected to partition to air.

Environmental Fate: Environmental processes, such as oxidation, the presence of acids or bases and microbiological processes, may transform insoluble metals to more soluble ionic forms. Environmental processes may enhance bioavailability and may also be important in changing solubilities.

Aquatic/Terrestrial Fate: When released to dry soil, most metals will exhibit limited mobility and remain in the upper layer; some will leach locally into ground water and/ or surface water ecosystems when soaked by rain or melt ice. A metal ion is considered infinitely persistent because it cannot degrade further. Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways |Ecotoxicity:|Fish LC50 (96h): 43mg/l

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
sodium hydroxide	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
sodium hydroxide	LOW (LogKOW = -3.8796)
Mobility in soil	

Ingredient	Mobility
sodium hydroxide	LOW (KOC = 14.3)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: Reduction Reuse Recycling Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Product / Packaging DO NOT allow wash water from cleaning or process equipment to enter drains. disposa It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Recycle wherever possible. · Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Mixing or slurrying in water; Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).

SECTION 14 TRANSPORT INFORMATION

Labels Required Marine Pollutant NO HAZCHEM 2W Land transport (ADG) UN number 1823 UN proper shipping name SODIUM HYDROXIDE, SOLID Class 8 Transport hazard class(es) Subrisk Not Applicable Packing group П Environmental hazard Not Applicable Special provisions Not Applicable Special precautions for user Limited quantity 1 kg

Air transport (ICAO-IATA / DGR)

UN number	1823		
UN proper shipping name	Sodium hydroxide, solid		
Transport hazard class(es)	ICAO/IATA Class 8 ICAO / IATA Subrisk Not Applicable ERG Code 8L		
Packing group	11		
Environmental hazard	Not Applicable		
Special precautions for user	Special provisions	Not Applicable	
	Cargo Only Packing Instructions	863	
	Cargo Only Maximum Qty / Pack	50 kg	
	Passenger and Cargo Packing Instructions	859	
	Passenger and Cargo Maximum Qty / Pack	15 kg	
	Passenger and Cargo Limited Quantity Packing Instructions	Y844	
	Passenger and Cargo Limited Maximum Qty / Pack	5 kg	

Sea transport (IMDG-Code / GGVSee)

UN number	1823
UN proper shipping name	SODIUM HYDROXIDE, SOLID
Transport hazard class(es)	IMDG Class 8 IMDG Subrisk Not Applicable
Packing group	Ш
Environmental hazard	Not Applicable
Special precautions for user	EMS Number F-A, S-B Special provisions Not Applicable Limited Quantities 1 kg

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

SODIUM HYDROXIDE(1310-73-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Sta	andards		Australia
Australia Hazardous S	ubstances	Information System - Consolidated Lists	

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (sodium hydroxide)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Υ
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

Name	CAS No
sodium hydroxide	1310-73-2, 12200-64-5

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at: $\underline{www.chemwatch.net}$

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit. IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.